

### PS63 - Height Endurance Vented Helmet

**Collection:** Head Protection

**Range:** PPE

**Materials:** ABS

**Outer Carton:** 20

#### Product information

Our premium Height Endurance Helmet is available in a vented version, for extra air flow. Light, comfortable and compact, this peak-less helmet is designed to be used when working at heights. Clever features include an ABS shell, 6-point textile suspension harness, wheel ratchet adjustment, size 52-63cm. Technical sweatband and 4-point chin strap (Y style) with a soft rubber chin protector included.

#### Head Protection

Portwest's head protection range aims to benefit our customers by combining the most up to date styles and standards in head protection, irrespective of job or location. Innovative, comfortable and lightweight helmets available for multiple uses.

#### PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

#### Standards

EN 397 (-30°C / +50°C)

ANSI/ISEA Z89.1 TYPE I (Class C)



#### Features

- Specially designed for working at height
- Vented helmet shell to allow air circulation cooling the wearer's head
- 6-point textile suspension harness for enhanced wearer comfort and safety
- Size adjustable headband via wheel ratchet system
- Y-style 4-point chin strap
- Light and robust
- Hi-Visibility colour for visibility in daylight
- Compatible with PW47 and PS47 clip-on ear muff
- Compatible with PS58 helmet visor holder
- Up to 7 years lifetime from manufacturing date (as long as undamaged)
- CE certified

**PS63 - Height Endurance Vented Helmet**  
**Commodity Code: 6506101000**

**Test House**

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)  
Bracetown Business Park  
D15 YN2P, Ireland  
Cert No: 2777/25167-01/E00-00

**Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	DUN14
PS63ORR	Orange	57.0	45.0	50.0	0.5200	0.1283	5036108309139	15036108797797