

PS73 - Height Endurance Mountaineer Helmet

Collection: Head Protection

Range: PPE

Materials: ABS, EPS (Expanded Polystyrene)

Outer Carton: 20

Product information

Height Endurance Mountaineer helmet is the ultimate evolution of our Height Endurance range. This vented, peak-less helmet is designed for multi-purposes. It is ideal for working at height, rescue operations and climbing activities. Thanks to its inner EPS foam, this style is fully certified to the EN 12492 standard. Its comfortable sweatband and wheel ratchet adjustment ensure optimal fit. Wide range of accessories available.

Head Protection

Portwest's head protection range aims to benefit our customers by combining the most up to date styles and standards in head protection, irrespective of job or location. Innovative, comfortable and lightweight helmets available for multiple uses.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Standards

EN 12492

EN 397 (Impact/Penetration/-30°C)

ANSI/ISEA Z89.1 TYPE I (CLASS C)



Features

- Specially designed for working at height
- Y-style 4-point chin strap
- Size adjustable headband via wheel ratchet system
- Inner expanded polystyrene foam
- Hi-Visibility colour for visibility in daylight
- Light and robust
- Compatible with PS58 helmet visor holder
- Up to 7 years lifetime from manufacturing date (as long as undamaged)
- Compatible with PW47 and PS47 clip-on ear muff
- CE certified
- UKCA marked

PS73 - Height Endurance Mountaineer Helmet
Commodity Code: 6506101000

Test House

Dolomiticert Scarl (Notified Body No.: 2008)
Zona Industriale Villanova, 7/A
, Italy
Cert No: EC 20-0013

SATRA Technology Centre Ltd (Notified Body No.: AB: 0321)
SATRA Technology Park
NN16 8SD, United Kingdom
Cert No: AB0321/19705-01/E00-00

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
PS73ORR	Orange	57.0	45.0	50.0	0.4980	0.1283	5036108325863	15036108814654