

ASM 18-3 PC

Precision cordless screwdriver, mid-mounted handle, up to 27 [3] in/lbs[Nm]

Parameterisable cordless screwdriver with mechanical shut-off clutch for industrial use.

Product number: 7 112 77 60 09 0



Details

- > Process-capable according to ISO 5393, VDI/VDE 2647, CmK value > 1.67 at $\pm 10\%$ (based on 6 Sigma).
- > For soft and hard screwdriving applications.
- > Programmable parameters (up to 5 increments): speed, direction of rotation, angle of rotation, torque threshold, time.
- > Adjustable error criteria prevent manipulation of the screwdriving process.
- > Infinitely variable speed setting.
- > Forward / reverse running can be parameterized.
- > Brushless motor with 30% greater efficiency and long service life.
- > High speed stability for constant work progress.
- > Full resilience in continuous operation up to maximum drive torque.
- > Extra-short construction for use in narrow spaces.
- > Low-fatigue working with slim grip and good balance.
- > Optimized air guide: Air does not blow onto hand or in face.
- > Extra-large, bright signal unit (OK / NOK).
- > Optimal screwdriving site illumination.
- > Wear-free accelerator switch.
- > Tool color-coded via coding rings.
- > Attachment option for hanger (balancer).
- > Integrated screw counter for setting maintenance interval.
- > Tool with storage battery charging status indicator (can be set).
- > MultiVolt-interface. Cordless tool can be used with all FEIN li-ion batteries (12-18 V).

Price includes

- ✓ Delivery does not include battery, charger or torque wrench.



Technical data

TECHNICAL DATA

Battery voltage

18 V

Battery interface

MultiVolt

Torque range

4 [0.5] - 27 [3] in/lbs[Nm]

No load speed

110 - 1,200 rpm

Tool mount

1/4 in Hexagon socket

Weight without battery

1.76 [0.80] lbs[kg]