



Bronze Ball Valve

2 Piece, Full Port, Solder Connection, Stainless Steel Trim, Insulated Handle, 600 CWP, 150 WSP

S-200CSS-IH




FEATURES


Dezincification Resistant Bronze Blow-Out Proof Stem Heavy Commercial Pattern 100% Leak Tested 29 in-Hg Vacuum Rating

CERTIFICATIONS/APPROVALS

ASME/ANSI B16.18 Meets MSS SP-110

VALVE SEAT RATING





MATERIALS

No.	Part	Material				
1	Body	Bronze - C84400				
2	Tailpiece	Bronze - C84400				
3	Ball	Stainless Steel 316				
4	Stem	Stainless Steel 316				
5	Packing Nut	Brass - C36000				
6	Seat (2)	PTFE				
7	Packing Gland	PTFE				
8	Thrust Washer	PTFE				
9	Handle Nut	Steel - Geomet® Plated				
10	Slide	Chrome Plated Steel				
11	Base Plate	Chrome Plated Steel				
12	Foam Insert	Polystyrene				
13	Handle	Nylon				
14	Cap	LDPE				
15*	Sleeve	CAB Tubing				

^{*}Not Pictured

DIMENSIONS

Part No	Size	Α	В	С	D
200-803-IH	1/2"	2.59	4.36	4.25	0.50
200-804-IH	3/4"	3.36	4.65	4.25	0.75
200-805-IH	1"	4.19	4.82	4.25	0.98
200-806-IH	1-1/4"	4.46	4.99	4.25	1.24
200-807-IH	1-1/2"	4.97	5.55	5.51	1.50
200-808-IH	2"	6.02	5.85	5.51	1.97